

LEAKDOWN DETECTION

What sets the Vacucheck $^{\text{\tiny{M}}}$ apart from any other vacuum tester on the market are its two built-in non-return valves that actually hold the vacuum that it creates.

Once the vacuum is created, the built-in valves shut automatically and the vacuum is held within a totally airtight volume.

The gauge of the Vacucheck™ is installed in line within a totally airtight volume.

The gauge of the Vacucheck™ is installed in line with the above mentioned circuit and allows the Vacucheck™ user to measure any leak accurately, regardless of its size, including micro-leaks that tipically go unnoticed.


True leak detection can only occur after the pump is stopped.

Only Vacucheck™ lets you measure the leakdown time and detect leaks.

A two step process:

- 1. Create the vacuum
- 2. Monitor leak

Vacucheck™, another NEWEN® innovation....



■ VAC100

The VACU-CHECK™ comes in a sturdy, yet light-weight car-rying case, with 8 pads and two in-line filters. It is easy to carry, fits comfortably in your hand and only requires an airline to be operated.

TECHNICAL CHARACTERISTICS

Compressed Air:

 Pressure:
 70 to 90 PSI (5 to 6 bars)

 Air Flow:
 1.12 cfm (0.53 l/second)

Depression:

Maximum Vacuum: 28.1" Hg (-94kPa) Time for evacuation of 1 liter of air

14.94" Hg (-50kPa) = 2 seconds 23.91" Hg (-80 kPa) = 5 seconds

Sound level: 60 dB(A)

Temperature: $-4^{\circ}F$ to $+176^{\circ}F$ ($-20^{\circ}C$ to $+80^{\circ}C$)

Email: contact@newen.com - Website: www.newen.com





■ VAC301
Replacement plexiglass plate Round
Diameter: 42mm (1.6535")




■ VAC302
Replacement plexiglass plate Round
Diameter: 45mm (1.7716")




■ VAC303
Replacement plexiglass plate Round
Diameter: 57mm (2.2441")




■ VAC304
Replacement plexiglass plate Round
Diameter: 70mm (2.7559")



■ VAC305
Replacement plexiglass plate Round
Diameter: 80mm (3.1496")



■ VAC306
Replacement plexiglass plate
Rectangular
Dimensions: 50mm x 80mm
(1.9685" x 3.1496")



■ VAC307
Replacement plexiglass plate Rectangular
Dimensions: 55mm x 65mm (2.1654" x 2.5591")



■ VAC308
Replacement plexiglass plate
Rectangular
Dimensions: 70mm x 90mm
(2.7559" x 3.5433")



■ VAC323
Replacement in-line filter (unit: one filter).



■ VAC329
Replacement vacuum chip.



■ VAC330
Replacement gauge.



■ VAC308
Plexiglass Plate
Rectangular
Dimensions: 101.6mm X101.6mm
(4" x 4")



■ VAC311
Replacement pre-cut self-adhesive foam pad set (100% compatible with Serdi pads).



■ VAC326
Aluminum plug for plexiglass plates.



VAC322Quick Connection with rubber tip for closed circuit.



■ VAC332
Replacement O-ring set.